



Entry control for home and office



Touch screen controller REGIS H-3-B



Regis H-3-B

- Controller with 4" LCD touch screen display
- Built-in proximity cards reader (13,56MHz)
- Regis H can be used as an access controller, T&A controller, human interface, etc.
- Designed for office buildings, financial institutions, hospitals, industry, R&D facilities, clubs, etc.
- Internal memory for 30.000 cards (expandable to 100.000) and 100.000 events
- RS-485 and TCP/IP communication as standard
- Push button and door status inputs, transistor output (0,5 A)
- Built-in accelerometer (anti-tamper protection)
- For vertical (default) or horizontal installation
- Keypad layouts for access control or T&A applications are available

TECHNICAL DATA

- **Dimensions:** 85x126x19 mm
- **Backlit 4,3" LCD touch screen (resistive)**
- **Resolution** 480 x 270
- **Reading frequency:** 13,56 MHz
- **Reading range:** up to 7 cm
- **Internal memory** for 30.000 cards (expandable to 100.000) / 100.000 events
- **RS-485 and TCP/IP communication**
- **RTC (real time clock) with battery back-up**
- **External power supply** 9 to 14 V DC (Spider W5, Spider W5-B, Spider W40, Spider W40-B, Spider H20, Spider H20-B)
- **Door status and push button inputs**
- **Door strike output (transistor, 0,5 A)**
- **Built-in accelerometer (anti-tamper alarm)**
- **IP 21 protection** – for indoor installation
- **Operating temperature:** from -20° to +50° C
- **Power consumption** 3 W (in ECO mode: 2 W)

ORDERING CODE

Code	Specification
REGIS H-3-B	4,3" touch screen controller in H-type housing, 13,56MHz