



Entry control for home and office



Touch screen controller REGIS T-3-B



Regis T-3-B

- Controller with 7" LCD touch screen display
- Built-in proximity cards reader (13,56MHz)
- Block connectors for optional additional external card reader
- Regis T can be used as an access controller, T&A controller, human interface, etc.
- Designed for office buildings, financial institutions, hospitals, industry, R&D facilities, clubs, etc.
- Internal memory for 30.000 cards (expandable to 100.000) / 100.000 events
- RS-485 and TCP/IP communication + Spider functionality as standard (it can be used as RS-485/TCP/IP communication converter for multiple additional controllers)
- Push button and door status inputs
- Door strike output
- Built-in accelerometer (anti-tamper protection)
- Vertical or horizontal installation
- Keypad layouts for access control or T&A applications are available

TECHNICAL DATA

- **Dimensions: 210x150x35 mm**
- **Backlit 7" LCD touch screen (capacitive)**
- **Resolution 1024 x 600**
- **Reading frequency: 13,56 MHz**
- **Reading range: up to 7 cm**
- **Memory for 30.000 cards (expandable to 100.000) / 100.000 events**
- **RS485 and TCP/IP communication + Spider functionality**
- **RTC (real time clock) with battery back-up**
- **External power supply 9 to 14V DC (Spider W5, Spider W5-B, Spider W40, Spider W40-B, Spider H20, Spider H20-B)**
- **Door status and push button inputs**
- **Door strike output (transistor, 0,5 A)**
- **Built-in accelerometer (anti-tamper alarm)**
- **IP 21 protection – for indoor installation**
- **Operating temperature: from -20° to +50° C**
- **2W speaker**
- **Power consumption 4 W (in ECO mode: 3 W)**

ORDERING CODE

Code	Specification
REGIS T-3-B	7" touch screen controller T-type housing, 13,56MHz