



Jantar

Entry control for home and office



Special access controllers for hotel or B&B applications

(13,56 MHz)



Rex O-3-H



Rex K-3-H



- Special single door access controller with built-in proximity cards and tags reader, with or without capacitive numeric keypad
- In O/K A-type housing for surface installation
- Reading frequency 13,56MHz
- For hotel rooms entrance control
- Designed for hotels, B&B or holidays rental apartments
- RS-485, TCP/IP and Bluetooth communication
- Internal memory for 20 cards /tags /codes and 1000 events
- Door status and push buttons inputs, transistor door strike output
- Signalization of the door status by changing the colour of hand logo (red/green flashing - locked, green - unlocked, red - error) or by changing the color of the keypad (amber - locked, green - unlocked, red - error)
- Programming with Codeks Apartment Kit software or with Codeks AC V10 / TA V10 + Codeks Hotel add-on

TECHNICAL DATA

- **Dimension: 90 x 90 x 17 mm**
- **Reading frequency: 13,56 MHz**
- **Reading distance: up to 5 cm**
- **Internal memory for 20 cards and 1000 events**
- **RS-485, TCP/IP and Bluetooth communication as standard**
- **IP45 protection**
- **External power supply 9 to 14 V DC (Spider W5-B, Spider W40, Spider W40-B, Spider H20, Spider H20-B)**
- **Anti-tamper alarm**
- **Operating temperature: from -20° to +40° C**
- **Max. current consumption: 0.2 A**
- **Signalization of the door status by changing the colour of hand logo or the color of the keypad and buzzer**

ORDERING CODES

Code	Specification
REX O-3-H-4BNx	Single door hotel controller in O-A type housing, 13,56 MHz, RS-485, Bluetooth and TCP/IP communication
REX K-3-H-4BNx	Single door hotel controller with numerical keypad, in K-A type housing, 13,56 MHz, RS-485, Bluetooth and TCP/IP communication