



Entry control for home and office



## Standalone access controllers REX B (13,56 MHz)



**Rex A-3-B**



**Rex O-3-B**



**Rex K-3-B**



- Standalone controllers with built-in proximity cards reader and with or without keypad for entering numerical codes
- For smaller, price-oriented access control systems
- Designed for both private and residential buildings, hotels and B&B, offices, shops, garages, etc.
- For opening of the inside doors of the buildings, barriers, gates, for switching on/off alarm systems, etc.
- Suitable for mounting outdoors
- Internal memory for 1000 cards or codes / 10.000 events
- Real time clock and RS-485 communication
- Anti-tamper alarm
- In standalone mode set-up can be made with a master card or master code, in advanced mode access control software (Blocker, Codeks) must be used
- Optional conversion to an advanced reader with 26-bit Wiegand output

### TECHNICAL DATA

- **Dimensions:**
  - 120x96x15 mm (Rex A-3-B)
  - 58x120x15 mm (Rex O-3-B)
  - 58x120x18 mm (Rex K-3-B)
- **Reading frequency: 13,56 MHz**
- **Reading range: up to 7 cm**
- **Internal memory for 1000 cards or codes / 10.000 events**
- **IP65 protection - suitable for outdoor installation**
- **External power supply 9 to 14 V DC (Spider W5, Spider W5-B, Spider W40, Spider W40-B, Spider H20, Spider H20-B)**
- **Door status and push button inputs**
- **Door strike transistor output (0,5 A)**
- **Built-in accelerometer (anti-tamper alarm)**
- **Operating temperature: from -20° to +50° C**
- **Current consumption: up to 0,1 A**
- **LED and buzzer for door status signalization**

### ORDERING CODES

Code	Specification
<b>REX A-3-B</b>	Standalone controller in A-B type housing, 13,56 MHz
<b>REX O-3-B</b>	Standalone controller in O-B type housing, 13,56 MHz
<b>REX K-3-B</b>	Standalone controller with keypad in K-B type housing, 13,56 MHz

Rex A and O - with 8 x 0,22 alarm cable (50 cm)  
 Rex K - with 8 wires flat cable (25 cm)